











Lil' BUBBA® Antiquing Powder™

FOR SUPERIOR CONCRETE LANDSCAPE CURBING

*Specially formulated powdered color
for adding bold and rich accenting contrast
to machine formed concrete curb.*

- Dust powder on with a brush or dip stamping tools into powder.
- Use darker antiquing powder over lighter CurbMix™ base colors.

| | | | |
|---|--|---|--|
|  |  |  |  |
| Sandy Beige | Walnut Brown | Roman Clay | Autumn Red |
|  |  |  |  |
| Rustic Brown | Ash Gray | Slate Gray | Charcoal Gray |

INSTRUCTIONS FOR MIXING Lil' BUBBA® CURBCOLOR

- 1 Combine 4 x 5 gal buckets of concrete sand with 1 x 5 gal bucket of Portland Cement in CurbMixer™.
- 2 Add 1.5 oz. of Lil' BUBBA® CURBFIBER™.
- 3 Add desired number of doses of Lil' BUBBA® CURBCOLOR. (See CurbColor chips on other side.)
- 4 Allow CurbMixer™ to blend materials for at least 3 minutes.
- 5 Slowly add water until CurbMix™ is nearing zero slump consistency.
- 6 Add 2 - 4 oz. of Lil' BUBBA® COLORGUARD+™.
- 7 Add final water to desired zero slump consistency and allow to mix for 2 minutes.


After extruding curb use an industrial sprayer to lightly mist surface with Lil' BUBBA® CURBFILM™. Trowel curb surface as necessary. Apply stamp patterns using stamp tools and Lil' BUBBA® ANTIQUING POWDER™. Remove excess powder carefully with a leaf blower and apply two coats of Lil' BUBBA® CURBSEAL™. NOW STAND BACK AND ADMIRE YOUR BEAUTIFUL WORK.

HOW TO PLACE ORDERS FOR Lil' BUBBA® CURBCOLOR SYSTEM PRODUCTS

Online: LilBubba.com/shop

Email: begin@LilBubba.com

Phone: (800) 314-9984 (407) 658-2788 or Fax: (407) 472-4205

 Pick-up: 11516 Satellite Blvd. Orlando, FL 32837

This chart is a guide only. Actual results may differ due to a wide range of variables, including but not limited to cement brand and sand color. We suggest that you make samples using local sand and cement.